



NEW PUSHBUTTON KNOCKOUTS ///////////

Optimized for Stainless Steel



Specialized Knockout

Punch and notch in one easy step for fast pushbutton (oiltight) installation

New Die Design

Optimized depth for widest range of materials and drivers

Easy Assembly

Designed for use with any Greenlee hydraulic driver - no adapters required

Durable, High Grade Steel

Provides maximum life in mild and stainless steel

SPECIFICATIONS

Minimum pilot Hole Size	0.625"
Maximum Material	12 ga. Stainless Steel
Thickness	10 ga. Mild Steel

PUSHBUTTON KNOCKOUT SET	SIZE	PUNCH	DIE	DRAW STUD	NUT
KS-PB22	22.5 mm	KP-PB22	KD-PB22	0000	044450
KS-PB30	30.5 mm	KP-PB30	KD-PB30	DSPB	04445G



NEW KEYWAY PUNCH

Easy Notching in Stainless Steel

- · Quickly notch industry-size keyways in pre-punched holes
- Durable, high grade steel provides maximum life in mild and stainless steel
- · Designed for use with any Greenlee hydraulic driver

SPECIFICATIONS

Sizes	1/8" (3.2mm) & 3/16" (4.8mm) notches for 7/8" (22.5mm) & 1-7/32" (30.5mm) holes	
Capacity	10 ga. Stainless Steel & Mild Steel	

CAT NO.	UPC NO.	DESCRIPTION
KWSET	783310044321	Keyway Punch Assembly



KEYWAY NIBBLER

- Manually notch industry-size keyways in up to 10 ga. mild steel
- Eliminates time-consuming hand sawing and filing when installing pushbuttons

SPECIFICATIONS

Sizes	1/8" (3.2mm) & 3/16" (4.8mm) notches for 7/8" (22.5mm) & 1-7/32" (30.5mm) holes
Capacity	10 ga. Mild Steel

CAT NO.	UPC NO.	DESCRIPTION
720	783310265344	Keyway Nibbler



