

V-DETECT™

AC Voltage Detector



VOLTAGE DETECTION AT A SAFE DISTANCE.

The V-DETECT AC Voltage Detector provides first responders with a safety tool that will alert them to potentially dangerous high voltage in their work area.

THE V-DETECT DESIGN FEATURES:

Versatile, lightweight, water resistant housing and rugged design enables first responders to easily manipulate the V-DETECT Detector safely in the harshest conditions. All of this achieved while weighing less than one pound.



VDET-4

V-DETECT™

AC Voltage Detector




FEATURES

- Loud beeper and flashing LED lights indicate the presence of voltage
- Heartbeat signal assures that the V-DETECT Detector is on and looking for voltage
- Easy to use user interface with large buttons
- Rugged, durable and water resistant housing for outdoor use
- Rechargeable battery - a 15 minute charge will provide a full day of typical use, a full charge will provide one week of typical use



ORDERING INFORMATION

VDET-4/K13	AC Voltage Detector Kit; Includes PRX-CORD and PRX-XF Charging Cords, PT-VDET Proof Tester, and VDET-BAG Bag
VDET-4/K12	AC Voltage Detector Kit; Includes PRX-CORD and PRX-XF Charging Cords, PRX-HS Holster, PT-VDET Proof Tester, CS-DET Case and S-3H Hot Stick
VDET-4/K11	AC Voltage Detector Kit; Includes PRX-CORD and PRX-XF Charging Cords, PT-VDET Proof Tester and CS-DET Case
VDET-4/K10	AC Voltage Detector Kit; Includes PRX-CORD and PRX-XF Charging Cords, PRX-HS Holster, PT-VDET Proof Tester and CS-DET Case
VDET-4/K08	AC Voltage Detector Kit; Includes PRX-CORD and PRX-XF Charging Cords and CS-DET Case
VDET-4/K03	AC Voltage Detector Kit; Includes PRX-CORD and PRX-XF Charging Cords and VDET-BAG Bag
VDET-4	AC Voltage Detector with Rechargeable Battery; Includes PRX-HS Holster, PRX-XF Charging Cord and CS-DET Case
PRX-CORD	Charge Cord with 12VDC Automotive Jack
PRX-XF	115-240VAC Transformer to Plug PRX-CORD into 115-240VAC Wall Outlet
PRX-HS	Carrying Holster with Belt Clip and Restraining Strap
VDET-BAG	Padded, Zippered Carrying Bag with Strap; Holds VDET-4, PT-VDET, PRX-HS and Charging Cords
CS-DET	Carrying Case; Holds VDET-4, PT-VDET, PRX-HS and Charging Cords
PT-VDET	Proof Tester® Voltage Detector Tester; Tests the V-DETECT Prior to Use
S-2H	2' Fixed Length Hot Stick
S-3H	3' Fixed Length Hot Stick
S-4H	4' Fixed Length Hot Stick



SPECIFICATIONS

OPERATING VOLTAGE RANGES	Two standard voltage ranges - 50VAC - 4kVAC (LO) 4kVAC - 500kVAC (HI)
TYPICAL WARNING DISTANCE	5 in. from 50V conductor (LO range) 3 ft. from 4kV conductor (HI range) Higher voltages will result in greater detection distances
OPERATING TEMPERATURE	-20°F to +140°F (-29°C to +60°C)
OPERATING FREQUENCY	25Hz-400Hz
BATTERY LIFE	One week of typical daily use after full charge
DIMENSIONS	11"L x 3"W x 2"D (28 cm x 7.6 cm x 5 cm)
WEIGHT	11 oz. (0.31 kg)