

STRUT SLAYR Shear 30T

RIDGID



COMPLETE STRUT CUTTING SOLUTION



STRUT SLAYR / Shear 30T

RIDGID® and Greenlee® provide a complete strut cutting solution with the StrutSlayer™ and Shear 30T. Cut clean, burr-free strut anywhere on the jobsite with the flexible RIDGID StrutSlayer or cut a variety of materials for jobsite preparation with the Shear 30T. Both improve safety with ergonomic designs that eliminate exposure to saw blades and increase productivity with precision cuts that eliminate the need for rework.







PRECISE SHEARS WITH **BUILT-IN MEASURING GUIDES.**



CLEAN, BURR-FREE CUTS WITH POWERFUL OUTPUT.



EFFICIENT OPERATION WITH QUICK DIE CHANGING.



SAFER JOBSITES WITH ERGONOMIC DESIGN.



Get fab shop quality cuts in the field in 5 seconds or less.

- Clean, burr-free cuts eliminate the need for filing
- Built-in portability makes for easy transport
- Jobsite stability with RIDGID® TRISTAND®
- Minimal sparking means safer jobsites
- Measuring guide ensures precise, accurate cuts

SPECIFICATIONS

CUTTING CAPABILITY

Up to 12ga 1^5 /s" x 1^5 /s" (41 x 41 x 2.5 mm) or 1^5 /s" x 1^3 /1s" (41 x 21 x 2.5 mm) strut channel to the MFMA-4 Standard. Not for use with stainless steel strut.

WEIGHT OF HEAD

13 lbs. (5.8 kg) (including dies, not including press tool)

PRESS TOOL COMPATIBILITY

RIDGID Standard Series 32kN Press Tools (Such as the RP 350, RP 340, or RP 330). Not for use with RIDGID 320-E and CT-400 Press Tools.

CUT SQUARENESS

+/- 2° (Strut must extend past strut support)



AVAILABLE DEDICATED OR COMBO DIES



1⁵/₈" x ¹³/₁₆" (41 x 21 mm) Dedicated Die (Cat. #64033)



15/8" x 15/8" (41 x 41 mm) Dedicated Die (Cat. #64038)



15/8" x 13/16" (41 x 21 mm) 15/8" x 15/8" (41 x 41 mm) Combo Die (Cat. #64043)



KITS AND DIES

Catalog No.	Description	Weights	
		LB	KG
64118	StrutSlayr™ Head	10.45	4.74
64063	Kit, Head+Case+Combo Dies	19.76	8.96
64058	Kit, Head+Case+15/8" Dies	19.76	8.96
64053	Kit, Head+Case+13/16" Dies	19.76	8.96
64048	Case, Carrying-StrutSlayr	6.47	2.93
64043	Die Shear - Combo	2.84	1.29
64038	Die Shear - 1 ⁵ / ₈ "	2.84	1.29
64033	Die Shear - ¹³ / ₁₆ "	2.84	1.29

Shear 307 Maximize productivity from preparation to jobsite.

30-ton ram quickly shears through tough materials

- Laser-marked measuring guide delivers accurate cuts
- Quick die changing system ensures efficiency
- Eliminates hot metal shavings caused by traditional cutting methods
- Automatic die retraction makes for easy operation

SPECIFICATIONS

CUTTING APPLICATIONS

Strut, Back to Back Strut, Threaded Rod, DIN Rail, Legrand®, Angle Iron & Rebar

WEIGHT OF SHEAR 30T OPERATING FORCE 227 lbs (Includes shearing unit, mobile cart, and measurement arm)

30 Ton Ram

KIT CONFIGURATIONS

Description	Bare Kit (GLSSB)	Kit with 980 Pump (GLSS980KIT-B)	Kit with EHP Pump (GLSSEHPKIT-B)
Shearing Unit	©	©	©
Mobile Cart	©	©	©
Measurement Arm	©	©	©
980 Electric Hydraulic Pump		©	
EHP Battery Hydraulic Pump			©





15%" Back to Back Strut (Cat. #158DSTRT)



Up to 2" x 2" x 1/4"

(Cat. #14ANG-KIT)



¼", ¾", ½", ½", ¾6"
(2 slots ¾", 2 slots for ½")
THREADED ROD
(Cat. #1458TROD)

DIES FOR STRUT

Catalog No.	Description
158SSTRT	Dual-Profile Strut $ 1^5$ /8" & 13 /16" x 1^5 /8"
158STRDSTRT	$Strut - 1^5 /8" \times 1^5 /8"$
1316SSTRT	$Strut - {}^{13} \! /_{16} \texttt{"} \times 1^5 \! /_{8} \texttt{"}$
78SSTRT	Strut — 1/8"x 15/8"
158DSTRT	Back to Back Strut $-1^5/_8$ "
1316DSTRT	Back to Back Strut $ ^{13}/_{16}$ "
78DSTRT	Back to Back Strut $-\%$ "
4STRT21	4Dimension [™] 4D21 Channel
4STRT22	4Dimension 4D22 Channel

DIES FOR OTHER MATERIALS

Catalog No.	Description
1458TROD	Threaded Rod $-\frac{3}{8}$ ", $\frac{1}{4}$ ", $\frac{1}{2}$ ", $\frac{5}{8}$ "
3000SSRB	Legrand – 2¾" (Cover)
3000SSRC	Legrand – 2¾" (Cover)
THDR7515	DIN Rail Combo Die – 7.5mm & 15mm x 35mm
GSDR15	DIN Rail — G-Section
*14ANG-KIT	Angle Iron — Up to 2" x 2" x $\frac{1}{4}$ " (Support system included)
*26RBR-KIT	Rebar — Up to #6 (Support system included)

^{*}A support system is required when cutting angle iron and rebar.

⁴Dimension is a trademark of Eaton Corporation.

Legrand is a registered trademark of Legrand





Learn more at RIDGID.com and Greenlee.com

